

APP CRS	Rwy Idg	11000
283°	TDZE	23
	Apt Elev	31

RNAV (RNP) Y RWY 28L


PORTLAND INTL (PDX)

▼ For uncompensated Baro-VNAV systems, procedure NA below -7°C (20°F) or above 54°C (130°F). For inop MALSR, increase RNP 0.23 all Cats visibility to RVR 5600 and increase RNP 0.30 all Cats visibility to 1½ mile. Simultaneous approach authorized with Rwy 28R. RF required. GPS required. Use of FD or AP providing RNAV track guidance required during simultaneous operations.



MALSR


MISSED APPROACH: Climb to 2100 then climbing left turn to 4000 direct UBG VOR/DME and hold.

D-ATIS	PORTLAND APP CON	PORTLAND TOWER		GND CON	CLNC DEL	CPDLC
128.35	124.35 299.2	Rwy 10L-28R	Rwys 3-21, 10R-28L			
269.9		118.7 257.8	123.775 251.125	121.9 348.6	120.125 318.1	



ELEV 31	D	TDZE 23
---------	---	---------



2100 ↑	4000 ↙	UBG 	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 72).			
See planview for multiple IF locations.			MUBAE	EVIDE	CATMI	
			PULOE	1500	1900	
			743	1082		
			2.1 NM	1.1 NM	1.3 NM	1.9 NM
CATEGORY	A		B	C		D
RNP 0.23 DA			370/33	347 (400-5%)		
RNP 0.30 DA			476/53	453 (500-1)		
AUTHORIZATION REQUIRED						

NW-1, 22 FEB 2024 to 21 MAR 2024

NW-1, 22 FEB 2024 to 21 MAR 2024