

LOC I-HFE 111.7	APP CRS 281°	Rwy ldg 10102 TDZE 1174 Apt Elev 1203
---------------------------	------------------------	--

ILS or LOC RWY 28R


PITTSBURGH INTL (PIT)

From NASTY: Radar required for procedure entry.
Radar required for LOC only.

MALSR MISSED APPROACH: Climb to 1800 then climbing right turn to 5000 direct EWC VOR/DME and hold.

∇ Simultaneous approach authorized. For inop ALS, increase S-ILS 28R Cat E visibility to RVR 4000 and S-LOC 28R Cats C/D/E visibility to RVR 5500. DME from **▲** MMJ DME. Simultaneous reception of I-HFE and MMJ DME required.



D-ATIS ARR 127.25 DEP 135.9	PITTSBURGH APP CON 123.95 360.8	PITTSBURGH TOWER 128.3 291.7	GND CON SOUTH 121.9 348.6 NORTH 127.8 348.6	CLNC DEL 126.75 353.7
---	---	--	---	---------------------------------



NE-4, 22 FEB 2024 to 21 MAR 2024

NE-4, 22 FEB 2024 to 21 MAR 2024

ELEV 1203	D	TDZE 1174
------------------	----------	------------------



REIL Rwy 10C HIRL all Rwys TDZ/CL Rwys 10L, 10R, 28L, 28R, 28C, and 32
FAF to MAP 5.6 NM
Knots Min:Sec 60 90 120 150 180 5:36 3:44 2:48 2:14 1:52

CATEGORY	A	B	C	D	E
S-ILS 28R	1374/18 200 (200-½)				
S-LOC 28R	1540/24	366 (400-½)	1540/35 366 (400-¾)		
C CIRCLING	1700-1	497 (500-1)	1880-2 677 (700-2)	1880-2¼ 677 (700-2¼)	1880-2½ 677 (700-2½)