


APP CRS	Rwy ldg	7614
306°	TDZE	57
	Apt Elev	62

RNAV (RNP) Z RWY 30L

NORMAN Y MINETA SAN JOSE INTL (SJC)

RNP AR APCH.	MALSR	MISSED APPROACH: Climb to 2000 on track 306° to ARTAQ and hold.
For uncompensated Baro-VNAV systems, procedure NA below 1°C or above 54°C. For inop ALS, increase RNP 0.10 all Cats visibility to RVR 5500 and increase RNP 0.30 all Cats visibility to 1½ SM.		

D-ATIS	NORCAL APP CON	SAN JOSE TOWER ★	GND CON	CLNC DEL	CPDLC	UNICOM
126.95	120.1 290.25	124.0 (CTAF) 257.6	121.7	118.0		122.95



ELEV 62	D	TDZE 57	2000	ARTAQ	VGSI and RNAV glidepath not coincident (VGSI Angle 3.00/TCH 70).	WOXAR
			tr 306°			1600
			See planview for multiple IF locations.			
			RW30L	306°		GP 3.00°
			4.7 NM		TCH 54	
CATEGORY	A	B	C	D		
RNP 0.10 DA		430/35	373 (400-½%)			
RNP 0.20 DA		464/40	407 (500-¾%)			
RNP 0.30 DA		541/50	484 (500-1)			
AUTHORIZATION REQUIRED						