WAAS	APP CRS	Rwy Idg	8005
CH 99732	101°	TDZE	38
W10A		Apt Elev	40

RNAV (GPS) RWY 10

WALLOPS FLIGHT FACILITY (WAL)

DME/DME RNP -0.3 NA. Rwy 10 helicopter visibility reduction below ¾ SM NA. When local altimeter setting not received, use Salisbury altimeter setting and increase all DA 60 feet and all visibilities ¼ SM. Increase all MDA 60 feet and all Cat C and D visibilities ¼ SM. Baro-VNAV and VDP NA when using Salisbury altimeter setting. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -11°C (13°F) or above 54°C (130°F).

MISSED APPROACH: Climb to 700 then climbing left turn to 2000 direct MAGGO and hold.

ASOS	PATUXENT APP CON ★		WALLOPS TOWER ★		GND CON		CLNC DEL
119.175	127.95	314.0	126.5 (CTAF) L	306.975 (CTAF) L	127.875	269.325	121.7







CATEGORY	A	B	C	D
LPV DA	330-1	292 (300-1)		
LNAV/VNAV DA	443-1¼	405 (500-1¼)		
LNAV MDA	420-1	382 (400-1)	420-1⅛	382 (400-1⅛)
C CIRCLING	600-1	560 (600-1)	620-1½ 580 (600-1½)	860-2¾ 820 (900-2¾)

REIL all Rwys
HIRL Rwys 4-22, 10-28 and 17-35

NE-3, 22 FEB 2024 to 21 MAR 2024
NE-3, 22 FEB 2024 to 21 MAR 2024